

### **Amendments to the Claims**

This listing of claims will replace all prior versions, all listings, of claims in the application:

5

#### **Listing of Claims:**

1. (Currently Amended) A method for decrypting data received by a receiver, the  
10 receiver being in communication with a sender, comprising:  
receiving the encrypted data from the sender;  
searching a key-table of the receiver for a decryption key corresponding to  
the encrypted data;  
updating the key-table ~~according to the encrypted data~~ with the decryption  
15 key corresponding to the encrypted data from a master key-table and  
enabling a re-transmission mechanism of the sender when the  
decryption key is not stored in the key-table and the encrypted data is  
received successfully; and  
decrypting the encrypted data through utilizing the updated decryption key  
20 stored in the key-table.
2. (Original) The method of claim 1 further comprising using a Media Access  
Control (MAC) Address of the sender to search the key-table for the  
decryption key.  
25
3. (Original) The method of claim 1 further comprising triggering a system  
interrupt to notify a controller of the receiver if the decryption key is not  
stored in the key-table.
- 30 4. (Previously Presented) The method of claim 3 wherein the controller searches  
a master list for the decryption key and transfers the decryption key to the

key-table when receiving the system interrupt.

- 5      5. (Original) The method of claim 1 further comprising replacing a least frequently used decryption key in the key-list with the decryption key transferred in.
6. (Original) The method of claim 1 further comprising discarding the encrypted data when the decryption key is not stored in the key-table.
- 10     7. (Original) The method of claim 1 wherein the step of enabling a re-transmission mechanism comprises disabling the receiver from outputting an acknowledgement message to the sender to inform the sender of reception of the encrypted data.
- 15     8. (Original) The method of claim 1 being applied to a wireless LAN (WLAN) system.
9. (Original) The method of claim 1 wherein the receiver is a wireless network card inserted in a computer.
- 20     10. (Currently Amended) A method for decrypting data received by a receiver, the receiver being in communication with a sender, comprising:  
receiving an encrypted data from the sender;  
disabling an acknowledgement message which informs the sender of  
25        reception of the encrypted data and updating the key-table ~~according to the encrypted data~~ with the decryption key corresponding to the encrypted data from a master key-table when a decryption key is not stored in a key-table and the encrypted data is received successfully, wherein the decryption key corresponds to the encrypted data;  
30        receiving an re-transmitted encrypted data from the sender; and  
decrypting the encrypted data re-transmitted from the sender ~~through~~

utilizing the updated decryption key stored in the key-table.

- 5      11. (Original) The method of claim 10 further comprising using a Media Access Control (MAC) Address of the sender to search the key-table for the decryption key.
- 10      12. (Original) The method of claim 10 further comprising replacing a least frequently used decryption key in the key-list with the decryption key transferred in.
13. (Original) The method of claim 10 being applied to a wireless LAN (WLAN) system.
- 15      14. (Original) The method of claim 10 further comprising discarding the encrypted data when the decryption key is not stored in the key-table.
- 20      15. (Original) The method of claim 10 wherein the sender re-transmits the encrypted data if the sender does not receive the acknowledgement message, and the receiver decrypts the encrypted data re-transmitted from the sender.
- 25      16. (Currently Amended) An apparatus for decrypting data received by a receiver, the receiver being in communication with a sender, comprising:  
a key-table for storing a plurality of decryption keys; and  
a receiving controller, coupled to the key-table, configurable to  
receive an encrypted data from the sender,  
search the key-table for a decryption key corresponding to the encrypted data, enable a re-transmission mechanism of the sender when the decryption key is not stored in the key-table and the encrypted data is received successfully, update the decryption  
30      keys in the key-table ~~according to the decryption data with the~~  
decryption key corresponding to the encrypted data from a master

key-table when the decryption key is not stored in the key-table;  
and

decrypt the encrypted data according to the updated decryption key  
stored in the key-table.

5

17. (Original) The apparatus of claim 16 wherein the receiving controller discards  
the encrypted data when the decryption key is not stored in the key-table.

18. (Original) The apparatus of claim 16 wherein the receiving controller uses a  
10 Media Access Control (MAC) Address of the sender to search the key-table  
for the decryption key.

19. (Original) The apparatus of claim 16 wherein the receiving controller replaces  
a least frequently used decryption key in the key-list with the decryption key  
15 transferred in.

20. (Currently Amended) An apparatus for decrypting data received by a receiver,  
the receiver being in communication with a sender, comprising:  
a key-table for storing a plurality of decryption keys; and  
20 a receiving controller, coupled to the key-table, configurable to  
receive an encrypted data from the sender,  
search the key-table for a decryption key corresponding to the encrypted  
data, disable an acknowledgement message which informs the  
sender of reception of the encrypted data when the decryption key  
25 is not stored in the key-table and the encrypted data is received  
successfully,  
update the decryption keys in the key-table ~~according to the decryption  
data~~ with the decryption key corresponding to the encrypted data  
from a master key-table when the decryption key is not stored in  
30 the key-table, and  
decrypt the encrypted data according to the updated decryption key

stored in the key-table.

21. (Previously Presented) The apparatus of claim 20, wherein when the decryption key is not stored in the key-table and the encrypted data is received successfully, the receiving controller suspends the decrypt  
5 procedure until the re-transmitted encrypted data is received and the decryption key is updated.